



IJRTSM

INTERNATIONAL JOURNAL OF RECENT TECHNOLOGY SCIENCE & MANAGEMENT

“A REVIEW ON OF TURBINE INLET BIG SIZE BUTTERFLY VALVE”

Akhil Kumar¹, Gagan Varshney²

¹ P. G. Student, Department of Mechanical Engineering, Greater Noida Institute of Technology Greater Noida , UP, India

²Assistant Professor, Department of Mechanical Engineering, Greater Noida Institute of Technology Greater Noida , UP, India

akhildahiya21061992@gmail.com

gagan.me@gniot.net.in

ABSTRACT

Butterfly valves are widely used in various industries such as water distribution, sewage, oil and gas plants. The hydrodynamic torque applied on the butterfly valve disk is one of the most important factors which should be considered in their design and application. Although several methods have been used to calculate the total torque on these valves, most of them are based on the hydrostatic analysis and ignore the hydrodynamic effect which has a major role to determine the torque of the large-size valves. In this paper, we will revive the dynamic-valve-torque has been calculated for a large size butterfly valve under different conditions and also at the different opening angles of the valve disk.

Key Words: *Butterfly valve, Hydrodynamic, Hydrostatic analysis, Valve disk.*

I. INTRODUCTION

Hydro control is considered as a standout amongst the most efficient and non-dirtying wellsprings of vitality. Power age from the water is named as Hydroelectricity. Hydroelectricity implies power created by hydro control or from the utilization of the gravitational power of falling water or streaming water. A standout amongst the most well-known types of energy age since this type of vitality neither creates coordinate waste issue nor it is subjected to weariness.

Presently a day's more hydro electrical power plants being setup and revamped. Yet at the same time the outline and advancement of hydro electrical power plant depends on the conventional strategies. Accordingly there is a gigantic extent of use of cutting edge's procedure like limited component technique (FEM) for accomplishing greatest conceivable enhancement.

In any power plant valves for various reasons for existing are generally required. Regularly it is a closed off valve just before the turbine. Along these lines the turbine might be exhausted without discharging the pole or penstock. What's more the guide vane course is depresserised with the goal that spillage stream is stayed away from.

The butterfly valve is one of the kinds of stop gadgets most generally utilized in hydropower station and frameworks. Its utilization is favored as a result of their generally minimal effort, minimization, light weight, sensible water snugness and straightforwardness of operation.



Fig.1 Turbine inlet Valve

II. LITERATURE REVIEW

Cohn [1951]. Using data gave by past makers, Cohn tried to define force and stream coefficients considering thickness to width extent for different butterfly valve calculations, most of which were balanced. [1]

McPherson [1957] thought about various front line assortments of single unpredictable butterfly valves in incompressible tempestuous stream subject to free, lowered, and diligent channeling discharge approaches. McPherson found that for a given sort of foundation, the stream characteristics were not out and out iMPacted by either the condition of the sharp edge or by the end point except for the nearby open and shut positions, exclusively. Using a two dimensional arrangement of different symmetric butterfly valve front lines, cavitation was in like manner anticipated.[2]

Sarpkaya [1961] furthermore considered the force and cavitation credits of respected two-dimensional and essentially even butterfly valves by pondering a celebrated example of laminar uniform course through a balanced lamina (addressing the butterfly valve) be-tween two ceaseless dividers. Using these doubts, Sarpkaya could loosen up unpleasant responses for hydrodynamic force, cavitation, and stream coefficients for three dimensional butterfly valves using semi-careful conditions. [3]

Addy et al. [1985] coordinated a couple of little scope compressible stream attempts various things with sud-nest expansion plans for butterfly valve models to foresee mass stream rate and general weight characteristics. Additionally, a full size butterfly valve was built and attempted. The unexpected expansion courses of action were named three exceptional kinds of spouts: framed centering, pipe formed gathering and sharp-edge opening. It was assumed that the execution ascribes of the valve can be envisioned if the valve stream coefficient is known for a foreordained working weight extent. [4]

Eom [1988] working off created by examined the execution of butterfly valves as a stream regulator. From examined the stream characteristics of penetrated and non-penetrated butterfly valve circles and watched their execution to be in extraordinary simultaneousness with one another, beside at low sharp edge (opening) point assessments of around 10 degrees. He moreover considered the iMPact that blockage extents (region of hover to area of line or channel) had on butterfly valves as choking contraptions. Also, Eom could predict disaster coefficients satisfactorily well from blockage extents at Reynolds numbers in the extent of 104. [5]

Morris and Dutton [1989] likely researched the smoothed out force characteristics of butterfly valves using two dimensional planar models and three dimensional model valves at choked and un-choked working centers, and the results revealed the criticalness of the stream parcel and reattachment wonders on the smoothed out force credits of butterfly valves. [6]

Morris and Dutton [1991] moreover researched the working ascribes of two coMParable butterfly valves mounted in game plan, and a test assessment concerning the working characteristics of a butterfly valve downstream of a 90 degree

mitered elbow. [7]

Kimura et al. [1995] used free-smooth out and wing theory to show symmetric butterfly valves between limitless equal dividers in two estimations and used cure conditions to compensate for pipe divider conditions. The change conditions also required a reviewed opening edge and thickness of the circles, and uniform speed. Using the given two-dimensional models, force credits, pressure hardship, and cavitation of three-dimensional tests were envisioned and separated. While the overall case of force coefficients took after the exploratory data, the differences between the envisioned and real regards were broad. In later years since Kimura and Ogawa, intelligent and building bunches in the field of fluid movement and valve explore have placed more emphasis in Computational Fluid Dynamics (CFD), especially with the methodology of business CFD programming during the 1990s. [8]

Huang and Kim [1995] were a segment of the first to use business CFD programming to explore three dimensional stream portrayal of a symmetric butterfly valve (showed as a flimsy crease valve circle). Huang used CFD code FLUENT to duplicate a reliable incompressible stream with $k-\epsilon$ choppiness illustrating. Valve positions were replicated at openings of 30, 45, 60, 70, and 90 degrees. Huang moreover examined the length downstream of the valve in which stream would return to totally made conditions. In light of computational constraints, a by and large coarse work of a generally outrageous of 25,000 cells was used as an aspect of the CFD assessments. [9]

Huang moreover differentiated his mathematical results and the preliminaries finished by **Blevins [1984]**. The 45 degree case was seen to be the most satisfying with the preliminary data, while the rest required comprehension. [10]

Lin and Schohl [2004] used business CFD programming FLUENT to anticipate drag coefficients for a symmetric coin framed butterfly valve at opening edges in a ceaseless stream field with comes about got likely by Hoerner [1958]. Affectability of the results to choppiness show decision, accuracy of discretization plans, structure quality, and framework dependence were pondered as a significant part of the endorsement. Lin took a gander at $k-\epsilon$, $k-\omega$, and $k-\omega$ SST choppiness models and thought that the later model was supported for settling the Reynolds-showed up at the midpoint of Navier-Stokes conditions and that usage of a first solicitation discretization for the stream zone incited gauges inside and out higher than those from the subsequent solicitation plans. Stream coefficients changed well to test data as a rule, despite it should be seen that right exhibiting assessments between the exploratory arrangement and the mathematical model were difficult to organize. Lin similarly exhibited a 3.66 meter estimation butterfly valve inside a line at valve openings of 20, 40, 50,60, 70, 80, and 90 degrees with cavitation free conditions and incompressible stream using CFD. A computational work gauge included around 1.5 million tetra and hexa-segments. Weight drop over the valve was figured and foreseen stream coefficients facilitated respectably well with exploratory data gave by the United States Army Corps of Engineers (USACE) for a correspondingly shaped circle butterfly damper. [11] [12]

Tune et al. [2007, 2008] played out an essential investigation of broad butterfly valves, despite affirming three-dimensional preliminary data of a butterfly valve's weight drop, stream coefficient, and hydrodynamic force coefficient using comprehensively valuable CFD code CFX . The $k-\epsilon$ disturbance show was picked by Song since it does exclude the complex non-direct damping limits needed by various models. A work of around 1,000,000 cells was used with a region expanding eight line breadths upstream from the valve and approximately ten line separations across downstream. Cases were continue running for plate opening purposes of 5 to 90degrees in increases of 5 degrees. Generally, extraordinary results were obtained except for when the valve opening point was under 20 degrees. In the 20 degree case, contrasts among test and reenactment data were seen to be practically half. [13, 14]

Leutwyler and Dalton [2006,2008] played out a CFD consider in two and three estimations for symmetric butterfly valves in compressible fluids at various edges and over an extent of weight extents. The comprehensively helpful CFD code FLUENT was used with the accomPanying disturbance models: Spalart-Allmaras, $k-\epsilon$, and $k-\omega$. Leutwyler supported the $k-\epsilon$ disturbance show for its reasonable limits and direct computational costs. Despite assessing grid refinement, coefficients for lift, drag and force were endorsed against exploratory regards. [15, 16]

Henderson et al. [2008] assessed force and head loss of an even butterfly valve presented in a hydro-electric force delivering plan for steadfast stream at Reynolds amounts of solicitation 106. This was improved the circumstance valve opening edges of 10 to 80 degrees in 10 degree increments. The comprehensively valuable CFD programming ANSYS

CFX was affirmed using accumulated test data. In the assessment, Henderson used threatening to vacuum valves downstream in a penstock entry to envision extraordinary cavitation. The CFD stream zone loosened up from around 58 separations across (D) upstream and 15D downstream to ensure totally made stream conditions. Tetrahedral segments were used on the valve face to best model the butterfly valve features. Consequently, the amount of cells in the territory went from 2.2 million to 220 million. Henderson supported the Shear Stress Transport (SST) choppiness showed and found that for valve focuses more conspicuous than 20 degrees, the stream downstream from the valve was overpowered vehemently by uncertain vertical disrupting impacts. A normal vortex shedding repeat of around 1.3 Hz was assessed. Cases were continue running in which the CFD models had an even cutoff to upgrade plan time and one in which the whole model was used for a predictable and transient course of action, independently. [17]

Kulvant Singh Parmar, et. al [2015] Valves for hydro power ventures are introduced for wellbeing, upkeep, and shut-off, just as for stream and weight guideline. A Butterfly valve is a kind of stream control gadget, which is generally used to manage a liquid moving through a segment of line. This sort of valve is basically utilized as security valve, turbine gulf valve, and siphon valve for low to medium plan pressures. They are worked by oil water powered frameworks for opening and shutting or by shutting weight and water driven weight for opening. For turbine channel valves, oil weight can likewise be taken from the lead representative water driven oil framework. The fixing framework is of adaptable, flexible elastic/metal sort to decrease spillage to a base. Water course through the valve is conceivable in the two ways. The primary goal of this work is to investigations the alternative of manufactured variation for entryway and body instead of projected, decrease in the material of valve body and entryway by basic plan and FEM examination and advancement in the material of valve part. The 3D demonstrating to be performs for butterfly valve by utilizing CAD programming. Further the pressure and removal FEM examination of the butterfly valve to be performed by utilizing ANSYS apparatus to assess the improved result.[18]

Atul Shrivastava et. al. [2017] Valves for hydro power ventures are fitted for wellbeing, adjusting and fix, and stop stream of water, just as for stream and variety in pressure. A Valve utilized in hydel power plant is known as Butterfly valve and is a sort of stream control gadget; it is generally used to direct a liquid coursing through a segment of line. This sort of valve is essentially utilized as wellbeing valve, turbine delta valve, and siphon valve for low to medium weights. They are water powered frameworks and worked by oil for opening and shutting or with the assistance of weight and pressure driven weight for opening., oil weight can likewise be taken from the lead representative pressure driven oil framework For turbine bay valves. The covering framework or halting framework is of adaptable, movable elastic/metal sort to diminish spillage. Water move through the valve is conceivable in the two ways. The extent of this proposition is to examinations the alternative of manufactured variation for entryway and body instead of projected, decrease in the material of valve body and entryway by FEM investigation and enhancement in the material of valve segment. The 3D displaying is to be accomplished for butterfly valve by utilizing CAD programming. What's more, stress and removal FEM investigation of the butterfly valve is finished by utilizing ANSYS apparatus to assess the upgraded result.[19]

Ujjwal Kumar et. al. [2017] Butterfly valves are utilized to control release of liquids in penstock of hydropower plants or mechanical line organizations. It has a plate introduced in the middle of which can be made to pivot physically or consequently by pneumatic servomotors. These valves are likewise utilized as complete shut off valve. The plate of butterfly valve is exposed to weight of liquid streaming in pipes which attempts to distort it. The protection from this weight is offered by plate when stresses are instigated in it. For safe working of butterfly valves, it is essential that the burdens prompted don't surpass versatile breaking point else it will prompt its lasting misshapening. Accordingly it gets important to contemplate the anxieties created in butterfly valves for its legitimate working. In the current work, mathematical displaying of multi grid butterfly valve has been done in ICEM CFD and Pro E. At that point pressure conveyances on valve plate have been gotten in CFX for expressed valve opening. There after these weight disseminations are imported in APDL for given opening and afterward worries at valve plate and rib are acquired and studied.[20]

III. CONCLUSION

In this paper, commercial CFD software to investigate three dimensional flow visualization of a symmetric butterfly valve and the dynamic-valve-torque has been calculated for a large size butterfly valve under different conditions and disk opening angles using Computational Fluid Dynamics (CFD) methods. Moreover, the effects of disk shape and its deformation, surface roughness, upstream/downstream pressure variation and disk-offset value have been studied and now we will be study on Structure analysis with help of ANSYS software and check stress level with pressure boundary condition.

REFERENCES

- [1] Cohn, S.D., "Performance Analysis of Buttery Valves," J. Instruments and Control Systems, 24, pp. 880-884, 1951.
- [2] McPherson, M.B., Strausser, H.S., and Williams, J.C., "Buttery Valve Flow Characteristics," J. Hydraulics Division, 83(1), pp. 1-28. 1957.
- [3] Sarpkaya, T., 1961, "Torque and Cavitation Characteristics of Buttery Valves," J. Applied Mechanics, 28(4), pp. 511-518.
- [4] Addy, A.L., Morris, M.J., and Dutton, J.C., "An Investigation of Compressible Flow Characteristics of Buttery Valves," J. Fluids Engineering, 107(4), pp. 512-517, 1985.
- [5] Eom, K., "Performance of Buttery Valves as a Flow Controller," J. Fluids Engineering, 110(1), pp. 16-19. 1988.
- [6] Morris M. J. and Dutton J. C., 1989, "Compressible Flowfield Characteristics of Butterfly Valves", ASME J. Fluids Eng., 111, pp.400-407, 1989.
- [7] Morris M. J. and Dutton J. C., "An Experimental Investigation of Butterfly Valve Performance Downstream of an Elbow", ASME J. Fluids Eng., 113, pp.81-85, 1991.
- [8] Kimura, T., Tanaka, T., Fujimoto, K., and Ogawa, K. "Hydrodynamic Characteristics of a Buttery Valve - Prediction of Pressure Loss Characteristics," ISA Trans., 34(4), pp. 319-326, 1995.
- [9] Ogawa, K., and Kimura, T., "Hydrodynamic Characteristics of a Buttery Valve - Prediction of Torque Characteristics," ISA Trans., 34(4), pp. 327-333, 1995
- [10] Huang, C., and Kim, R.H., "Three-dimensional Analysis of Partially Open Butterfly Valve Flows," J. Fluids Engineering, 118(3), pp. 562-568. 1996.
- [11] Lin, F., and Schohl, G.A., "CFD Prediction and Validation of Buttery Valve Hydrodynamic Forces," Proceedings of the World Water and Environmental Resources Congress, pp. 1-8., 2004.
- [12] Hoerner, S., Fluid-Dynamic Drag: Practical Information on Aerodynamic Drag and Hydrodynamic Resistance, Hoerner Fluid Dynamics, CA. 1958.
- [13] Song, X., Wang, L., and Park, Y., "Fluid and Structural Analysis of Large Buttery Valve," AIP Conference Proceedings, 1052, pp. 311-314, 2008.

- [14] Song, X., and Park, Y.C., "Numerical Analysis of Butterfly Valve - Prediction of Flow Coefficient and Hydrodynamic Torque Coincident," In Proceedings of the World Congress on Engineering and Computer Science, pp. 759-763.2007.
- [15] Leutwyler, Z., and Dalton, C., "A Computational Study of Torque and Forces Due to Compressible Flow on a Butterfly Valve Disk in Mid-Stroke Position," J. Fluids Engineering, 128(5), pp. 1074- 1082.2006.
- [16] Leutwyler, Z., and Dalton, C., "A CFD Study of the Flow Field, Resultant Force, and Aerodynamic Torque on a Symmetric Disk Butterfly Valve in a Compressible Fluid," J. Pressure Vessel Technology, 130(2), .2008.
- [17] Henderson, A.D., Sargison, J.E., Walker, G.J., and Haynes, J.H., "A Numerical Prediction of the Hydrodynamic Torque Acting on a Safety Butterfly Valve in a Hydro- Electric Power Scheme," WSEAS Trans. on Fluid Mechanics, 1(3), pp. 218-223.2008.
- [18] Kulvant Singh Parmar, Yogesh Mishra "Structural Design and FEM Analysis of Large Butterfly Valve: A Review" International Journal of Engineering and Technical Research (IJETR) ISSN: 2321-0869, Volume-3, Issue-5, May 2015.
- [19] Atul Shrivastava , Arun Patel "STRUCTURAL DESIGN & FEM ANALYSIS OF LARGE BUTTERFLY VALVE "International Research Journal of Engineering & Applied Sciences, IRJEAS www.irjeas.org, ISSN(O): 2322- 0821, ISSN(P): 2394-9910, Volume 5 Issue 4, Page 25-30, Oct 2017-Dec 2017.
- [20] Ujjwal Kumar, Vishnu Prasad, Ruchi Khare "NUMERICAL COMPUTATION OF STRESSES ON BUTTERFLY VALVE" IJARSE, Vol 06, Issue 02, 2017.