RESEARCHERID THOMSON REUTERS [Ashish et al., 7(3),Mar 2022]

ISSN : 2455-9679 Impact Factor : 4.256



INTERNATIONAL JOURNAL OF RECENT TECHNOLOGY SCIENCE & MANAGEMENT

"DESIGN AND ANALYSIS OF RAILINGWIRE ROPE BY USING FEM"

Ashish Kumar¹, Sunil Chaturvedi²

¹ M.Tech. Scholar, Department of Mechanical Engineering, NIRT, Bhopal, MP, India ² Assistant Professor, Department of Mechanical Engineering, NIRT, Bhopal, MP, India

ABSTRACT

Crane is a hoisting device use for lifting and lowering load with means of drum or lift wheel around which there will be rope or chain wraps. EOT crane is a mechanical devices used for lowering or lifting material, also used for making the material move vertically or horizontally. It will be useful when the task is beyond the human capacity to moving or lifting the loads. By applying normal load FEA of all three Galvanized stainless steel 1*19 right lay wire rope were investigated here, with special concentration on different types of stresses and different types of deformation and strains, the contact type use here between the surfaces is bonded contact type. Discretization of elements are done with 3D brick solid elements with the aim to achieve suitably accurate results. Since there are not much paper in which this topic was analyzed.

Key Words: Crane, EOT, 3D, stainless steel, deformation and strains

I. INTRODUCTION

Crane is a hoisting device use for lifting and lowering load with means of drum or lift wheel around which there will be rope or chain wraps. EOT crane is a mechanical devices used for lowering or lifting material, also used for making the material move vertically or horizontally. It will be useful when the task is beyond the human capacity to moving or lifting the loads. Crane is a special design structure equipped with mechanical elements for load by lowering or raising by manual or electrical operation. Applications of cranes are generally in the transport industries for unloading and loading of load, in construction industries for the materials movement; and in manufacturing industries for assembling of heavy equipments. This device decreases the cost of the production by increase the output, speed up the deliveries & improve quality. Due to increase in labour costs and issues related to labour management the utility of this device has further been increased. Crane is very much useful in increasing human comfort by picking up load from one point and transport the object from one place to another. In designing of cranes there are three major considerations. First, the weight of load must be lifted up by the crane. Second, no topple of the crane. Third, rupture should not be there in crane. Cranes are available in lot of categories. They are called as Jib crane, Telescopic crane, Tower crane, Gantry crane, Truck mounted, Aerial crane, EOT crane, etc. The constructions of EOT cranes are typically of two types, either single girder or in double girder.

Fiber Core, it is constructed by synthetic material like polythene/poly- propylene strands (NYLON) ropes. Fiber cores are the most elastic & flexible, in which lubricant is bind. The advantage of fiber core is when there is a tensile load act on wire rope it crush the fiber as wire ropes diameter is reduces and the lubricant is comes out of the fiber and friction is reduced in between the wires. On the removal of load the core expands to its actual shape and absorb again the lubricants, but it have the downside. Whenever there is a temperature environment fiber cores are melts out

RESEARCHERID

THOMSON REUTERS



of the wire and also it getting crushed easily on applying heavy load



Fig 1 WR with Fiber Core

II. DESIGN PARAMETERS

Design Parameter for ordinary WRS

Table 1 Design parameter for ordinary WRS

Model	Specification
Centre wire dia.	2mm (No. of wires 1)
1 st layer wire dia.	2mm (No. of wires 6)
2 nd layer wire dia.	2mm (No. of wires 12)
strand dia	10mm
length	70mm
Lay Length	70mm
Fill factor	87.17%
Helix Angle	65.82 degree

Design Parameter for Warrington WRS

Table 2 Design parameter for Warrington WRS

Model	Specification
Centre wire dia.	2.1mm (No. of wire 1)
1 st layer wire dia.	2.1mm (No. of wires 6)
2 nd layer wire dia.(a)	2.35mm (No. of wires 6)
2 nd layer wire dia.(b)	1.75mm (No. of wires 6)
strand dia	10mm
length	70mm
Lay Length	70mm
Fill factor	82.38%
Helix Angle	65.82 degree

THOMSON REUTERS

[Ashish et al., 7(3),Mar 2022]

Design Parameter for Seale WRS

Model	Specification
Centre wire dia.	2.74mm (No. of wire 1)
1 st layer wire dia.	1.37mm (No. of wires 9)
2 nd layer wire dia.	2.585mm (No. of wires 9)
strand dia.	10mm
length	70mm
Lay Length	70mm
Fill factor	80.65%
Helix Angle	65.82 degree

Table 3 Design parameter for Seale WRS

III. DISCRETISATION OF IWSC

Selection of appropriate element type is necessary for the analysis. A three-dimensional brick solid element is to use as element for Discretization of structure. Or the selection of mesh density of an appropriate convergence studies are conduct, with aim to achieve suitable accurate results. It is a higher order 3D 20-nodes solid element which exhibits behavior of quadratic displacement. The element having three degrees of freedom per node: translations in the nodal x, y, and z directions. The element supports plasticity, creep, large deflection, hyper-elasticity, large strain capabilities and stress stiffening. It also has mixed formulation capability for simulating deformations of nearly incompressible elasto-plastic materials, and fully incompressible hyper-elastic materials. This type of element is well suited to modeling irregular meshes (such as those produced by various CAD/CAM systems), which was the case here. Meshing of independent wire strand, the overall elements and nodes in independent wire strands core are given below in the table, the discretization caused here is very well.



Fig 2 Meshing of Ordinary wire rope

http://www.ijrtsm.com@International Journal of Recent Technology Science & Management



Fig 3 boundary conditions or wire rope

Material used for wire rope:

Galvanized steel of Grade 37 is used as a material for the wire ropes, the typical material composition is (Carbon 0.2% Phosphorous 0.1% Manganese 1.35% Sulphur 0.04%)

IV. RESULTS



Fig 4 Total deformation in ordinary wire rope









Fig 5 Total deformation in Seale wire rope

V. CONCLUSION

The WR and their types are discussed. Wire rope applications and advantages are studied, and failures in WR are also discussed.

The objectives of the project were met as the analysis for failure of three WR with similar parameters has been done; comparative study between different properties has been done.By applying normal load FEA of all three Galvanized stainless steel 1*19 right lay wire rope were investigated here, with special concentration on different types of stresses and different types of deformation and strains, the contact type use here between the surfaces is bonded contact type. Discretization of elements are done with 3D brick solid elements with the aim to achieve suitably accurate results. Since there are not much paper in which this topic was analyzed. The wire ropes strands, as a

THOMSON REUTERS

[Ashish et al., 7(3),Mar 2022]

member of complex WR was subjected to axial loading.

- 1. The obtained results have good agreements with the analytical results calculated for ordinary wire rope.
- 2. The results obtained after analysis suggest that the stress generated at any particular load is least in Seale type wire rope and at most in ordinary type wire rope. So, the conclusion is that the load bearing capability is more in Seale type wire rope.
- 3. The equivalent strain generated in the Seale type wire rope is least and in ordinary is most, but the lateral deformation is more in Seale type but this is much within the limit and do not cause failure of the WR.
- 4. The wire rope first fail due to exceeding Yield stress limit and the reduction in diameter is not cross the limit here.

REFERENCES

- 1. Soji Yamakawa And Kenji Shimada "Fully-Automated Hex-Dominant Mesh Generation With Directionality Control Via Packing Rectangular Solid Cells "International Journal For Numerical Methods In Engineering Int. J. Numer. Meth. Engng 2003.
- D. Basak, S. Pal, And D. C. Patranabis "Nondestructive Evaluation Of A 6X25 FW Haulage Rope In A Monocable Continuously Moving Passenger Cable Car Installation" IACSIT International Journal Of Engineering And Technology Vol.1,No.5,December,2009.
- 3. ER.G.S. RAMTEKE AND PROF. Y.L.YENARKAR, Department Of Mechanical Engineering Rajiv Gandhi College Of Engineering Research Technology, Chandrapur "ANALYSIS OF WIRE ROPE" International Journal Of Engineering Research & Technology (IJERT) ISSN: 2278-0181, 2014.
- 4. Rakesh Sidharthan And Gnanavel, "Numerical Analysisof Independent Wire Strand Core (Iwsc) Wire Rope" International Journal Of Engineering Research & Technology ISSN: 2278-0181, Vol. 3, 2014.
- 5. Jie Tian, Junying Zhou*, Hongyao Wang & Guoying Meng "Literature Review Of Research On The Technology Of Wire Rope Nondestructive Inspection In China And Abroad"Publishedbyedpsciences,2015.
- Gordana Kastratović, Nenad Vidanović "3d Finite Element Modeling Of Sling Wire Rope In Lifting And Transport Processes "Transport ISSN 1648-4142/Eissn 1648-3480 2015 Volume 30(2).
- 7. Shaiful Rizam Shamsudin, Mohd Harun, Mazlee Mohd Noor, Azmi Rahmat, Rohaya Abdul Malek "Failure Analysis Of Crane Wire Rope" Materials Science Forum Vol 819 (2015) Pp 467-472, (2015).
- 8. Anubhav Sharma, Abhijeet Raut, Nilesh Awate, S.C.Sharma "A Review Paper Of Safety & Testing Of Over Head Crane" International Journal Of Innovations In Engineering And Science, Vol. 2, No.9, 2017.
- Urbi Pal*, Goutam Mukhopadhyay, Ankush Sharma, Sandip Bhattacharya "Failure Analysis Of Wire Rope Of Ladle Crane In Steel Making Shop "International Journal Of Fatigue Science Direct 116 (2018) 149– 155, 2018.
- 10. Ping Zhou , Gongbo Zhou ,Zhencai Zhu , Zhenzhi He , Xin Ding And Chaoquan Tang "A Review Of Non-Destructive Damage Detection Methods For Steel Wire Ropes" Appl. Sci. , MPDI 9, 2771, 2019.
- 11. Dabiao Liu, Shimin Zheng, Yuming He "Effect Of Friction On The Mechanical Behavior Of Wire Rope With Hierarchical Helical Structures" Sage Journals, 2019.